: 4/4 BLADE CUT : 1/5

TEARING

: 2/4

PUNCTURE **CUTTING BY SHARP**

FEATURES

- NYLON KNIT GLOVE, 13 GAUGE
- FULL BLACK NITRILE COATING
- **ELASTIC WRIST**
- LENGTH APPROX. 200 TO 260 MM DEPENDING ON SIZE

RECOMMENDED USES

- HANDLING GREASY, OILY PARTS
- AUTOMOTIVE INDUSTRY, **AERONAUTICS**
- MAINTENANCE OF MACHINE TOOLS, HOUSEHOLD APPLIANCES

CE MARKING

 THIS MARKING SIGNIFIES COMPLIANCE WITH THE ESSENTIAL REQUIREMENTS PRROVIDED FOR BY EUROPEAN REGULATION 2016/425, RELATING TO PERSONAL PROTECTIVE EQUIPMENT

SAFETY, COMFORT, AND DEXTERITY

- DEXTERITY: LEVEL 5
- THIS GLOVE DOES NOT CONTAIN ANY SUBSTANCE AT SUCH LEVELS AS TO BE KNOWN OR SUSPECTED OF HAVING ADVERSE EFFECTS ON THE HYGIENE OR HEALTH OF THE USER UNDER THE EXPECTED CONDITIONS OF USE

PACKAGING

- IN CASE OF DECONDITIONING, A COPY OF THE INSTRUCTIONS MUST BE ENCLOSED WITH THE SMALLEST **PACKAGING**
- **BAG OF 10 PAIRS**
- **BOX OF 100 PAIRS**





Guyard

PRECAUTIONS FOR USE

- WEAR GLOVES ON CLEAN, DRY **HANDS**
- IT IS RECOMMENDED TO CARRY **OUT A PRELIMINARY TEST UNDER** REAL CONDITIONS OF USE, WHICH MAY DIFFER FROM EU TYPE **TESTING**
- BEFORE RE-USE, CHECK GLOVES FOR DEFECTS, HOLES, TEARS, ABNORMAL WEAR, ETC

STORAGE AND MAINTENANCE

- STORE PRODUCTS IN A DRY, COOL, WELL-VENTILATED PLACE, AWAY FROM LIGHT, SUNLIGHT AND ULTRAVIOLET RAYS, AND IN THEIR ORIGINAL PACKAGING
- WHEN CORRECTLY STORED. **GLOVES RETAIN THEIR** PROPERTIES WITHOUT UNDERGOING SIGNIFICANT CHANGE
- NO SPECIAL MAINTENANCE IS RECOMMENDED
- **NOT WASHABLE**

LIMITATIONS OF PROTECTION

- DO NOT USE FOR HANDLING **OBJECTS AT TEMPERATURES** ABOVE 50°C
- DO NOT USE FOR HANDLING CHEMICALS OR LIQUIDS

GUYARD SAS 22-24, RUE LUCIEN ROUZET

Z.A. VILLEDIEU SUR INDRE/NIHERNE

36250 NIHERNE FRANCE

DISPOSAL

END-OF-LIFE DESTRUCTION MUST BE CONTROLLED AND COMPLY WITH EUROPEAN TRACEABILITY AND ENVIRONMENTAL REQUIREMENTS

EU TYPE CERTIFICATE ISSUED IN ACCORDANCE WITH MODULE B REGULATION (EU) 2016/425 - INTERTEK ON №2575 THE EU DECLARATION OF CONFORMITY IS AVAILABLE ON OUR WEBSITE: WWW.GUYARD-SA.COM

